



### Benefits

- ▶ 1U 17" LCD console drawer
- ▶ Dual slide - LCD and keyboard slide independently
- ▶ 1920 x 1080 native resolution / 16.7M colors ( 8-bit )
- ▶ DVI-D + VGA video input / USB KB / MS
- ▶ 104-key keyboard with touchpad
- ▶ One Man installation design
- ▶ Enhanced aesthetics with molded front handle and two point lock
- ▶ 2-year standard warranty ( upgradable up to 5 years )

### Options

- HDMI 1.4 + Audio input & output ( **AV4.4** )
- HDMI 1.4 video input ( **HDMI** )
- DP 1.0 video input \* ( **DP** )
- 3G / HD / SD-SDI Broadcast-grade input ( **SDI** )
- Composite ( **BNC** )
- DC power : 12V / 24V / 48V / 125V
- MAC or SUN Micro keyboard options available

\* No DVI-D after integration of DP 1.0 video input

## Product Specifications

### Console Port

Video input	VGA + DVI-D single link
KB / MS	USB interface
VGA console 6ft cable : CB-6A or DVI-D console 6ft cable : CX-6A	Drawer end : DB-15 + USB type A x 2 Server end : DB-15 + USB type A x 2  Drawer end : DVI-D + USB type A x 2 Server end : DVI-D + USB type A x 2

### LCD Panel

Panel size ( diagonal )	17.3"
Native resolution	1920 x 1080
Brightness ( cd/m <sup>2</sup> )	300
Contrast ratio ( typ. )	1000 : 1
Colors	16.7 M, 8-bit
Viewing angle ( L/R/U/D )	89/89/89/89
Response time ( ms )	25
Dot pitch ( mm )	0.1989
Display area ( mm )	381.888H x 214.812V
Surface treatment	Anti-glare, Hard-coating
Surface hardness	3H
Backlight type	LED
MTBF (hrs)	15,000

### Physical

Product ( W x D x H )	Single console	442 x 650 x 44 mm 17.4 x 25.6 x 1.73 inch
	Console w/ KVM	442 x 650 x 44 mm 17.4 x 25.6 x 1.73 inch
Packing ( W x D x H )	Single console /	590 x 815 x 140 mm
	Console w/ KVM	23.2 x 32.1 x 5.5 inch
Net weight	Single console	11.9 kg / 26.2 lb
	Console w/ KVM	12.9 kg / 28.4 lb
Gross weight	Single console	17.9 kg / 39.4 lb
	Console w/ KVM	18.9 kg / 41.6 lb

\* All dimensions stated are subject to change if options are selected / integrated to base model part codes

### Mounting Distance

Single console drawer / Console w/ KVM drawer	660 ~ 870 mm 26 ~ 34.3 inch
--	--------------------------------

### Video Option

Digital	HDMI	HDMI 1.4 / HDCP 1.4
	Display port	DP 1.0 / HDCP 1.3
Analog	Composite ( BNC )	NTSC & PAL

### Audio Option

Input	Connector	3.5mm stereo jack
	Impedance / Power level	30kΩ / 750mV
Output	Connector	3.5mm stereo jack
	Resistance / Power level	30kΩ / 2.8V
Speaker	Dual stereo	2W x 2

### Power

Input	Auto-sensing 100 to 240VAC, 50 / 60Hz	
Consumption (console / KVM)	Screen on	Max. 14W / Max. 45W
	Power saving mode	Max. 2W / Max. 34W
	Power button off	Max. 1W / Nil

### Environment

Operating temp.	0 to 55°C degree
Storage temp.	-20 to 60°C degree
Operating humidity	20~90%, non-condensing
Storage humidity	5 ~90%, non-condensing
Operating altitude	16,000 ft
Non-operating altitude	40,000 ft
Shock	10G acceleration ( 11ms duration )
Vibration	10~300Hz 0.5G RMS random vibration

### Compliance


EMC	FCC & CE
Safety	CE / LVD & UKCA
Environment	RoHS3 & REACH

# DF117 models w/ KVM


\*\* Resolution related to LCD specification

<b>2K KVM</b>	<b>IP</b>	<b>Remote</b>	<b>8-port</b>
	0	0	DF117 - 801D

**2K KVM Cable**



**CH - 6D** (6 ft)  
DVI-D KVM cable




**CH - 6H** (6 ft)  
HDMI KVM cable

Resolution Support \*\*: 16:9 - max. 2560 x 1440  
16:10 - max. 1920 x 1200  
4:3 - max. 1600 x 1200

<b>DVI-D KVM</b>	<b>IP</b>	<b>Remote</b>	<b>12-port</b>
	0	0	DF117 - 1201D

**DVI-D USB KVM Cable**


Resolution Support \*\*: 16:10 - max. 1920 x 1200  
16:9 - max. 1920 x 1080  
4:3 - max. 1600 x 1200




**CI - 6** (6 ft)  
**CI - 15** (15 ft)

<b>Cat6 Matrix KVM</b>	<b>IP</b>	<b>Remote</b>	<b>8-port</b>	<b>16-port</b>	<b>32-port</b>
	1	1	-	DF117 - MU1P1613	DF117 - MU1P3213
	2	1	-	DF117 - MU1P1624	DF117 - MU1P3224
	0	1	-	DF117 - MU1602	DF117 - MU3202
	0	2	-	DF117 - MU1603	DF117 - MU3203
	0	3	-	DF117 - MU1604	DF117 - MU3204


**Cat6 KVM Dongle**




**DG - 100C**  
USB-C dongle




**DG - 100P**  
DP - USB dongle



**DG - 100H**  
HDMI - USB dongle



**DG - 100SD**  
DVI - USB dongle




**DG - 100S**  
VGA - USB dongle

Resolution Support \*\*: 16:10 - max. 1920 x 1200  
16:9 - max. 1920 x 1080  
4:3 - max. 1600 x 1200


<b>Cat6 Combo KVM</b>	<b>IP</b>	<b>Remote</b>	<b>8-port</b>	<b>16-port</b>	<b>32-port</b>
	1	0	DF117 - UIP802	DF117 - UIP1602	DF117 - UIP3202
	0	1	DF117 - U802	DF117 - U1602	DF117 - U3202
0	0	DF117 - U801	DF117 - U1601	DF117 - U3201	

<b>DB-15 Combo KVM</b>	<b>IP</b>	<b>Remote</b>	<b>8-port</b>
	1	0	DF117 - IP802
	0	1	DF117 - 802
0	0	DF117 - S801	


**DB-15 VGA USB KVM Cable**



**CB - 6** (6 ft)




**CB - 10** (10 ft)





**CB - 15** (15 ft)

Resolution Support \*\*: 16:10 - max. 1920 x 1200  
16:9 - max. 1920 x 1080  
4:3 - max. 1600 x 1200

**IP Console**









**High Performance KVM Access Over IP**










Connector :	RJ45
User management :	1 x active user, 15-user login
Network protocol :	DHCP / BOOTP / DNS
Security :	TLS 1.3, AES, LDAP, Active Directory (AD), HTTP(s)
Browser :	Chrome, Firefox, Edge, etc.
Resolution :	16:9 - max. 1920 x 1080 / 16:10 - max. 1920 x 1200 / 4:3 - max. 1600 x 1200

## Standard Keyboard

**Ge** G keyboard with touchpad



### Supporting layouts

America						
	U.S.					
EMEA						
	U.K.	Germany	France	Russia	Spain	Italy
Asia						
	Japan	Korea				

## Keyboard Options

\* US layout only

**Me** Mac keyboard with touchpad



**Se** S keyboard with touchpad

